

US009410699B2

(12) United States Patent Satoh et al.

(54) COMBUSTION HEATER

(71) Applicants: **Kimiyoshi Satoh**, Tokyo (JP); **Soichiro Kato**, Tokyo (JP); **Shusaku Yamasaki**,
Tokyo (JP); **Kazuo Miyoshi**, Tokyo (JP)

(72) Inventors: Kimiyoshi Satoh, Tokyo (JP); Soichiro Kato, Tokyo (JP); Shusaku Yamasaki, Tokyo (JP); Kazuo Miyoshi, Tokyo (JP)

(73) Assignee: IHI CORPORATION (JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 320 days.

(21) Appl. No.: 14/149,120

(22) Filed: Jan. 7, 2014

(65) **Prior Publication Data**

US 2014/0116424 A1 May 1, 2014

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2012/068826, filed on Jul. 25, 2012.

(30) Foreign Application Priority Data

Jul. 27, 2011 (JP) 2011-163867

(51) Int. Cl. F23D 14/12 (2006.01) F23D 14/02 (2006.01) F23D 14/74 (2006.01) F23D 14/58 (2006.01) (Continued)

(52) U.S. Cl.

CPC *F23D 14/125* (2013.01); *F23C 3/006* (2013.01); *F23D 14/02* (2013.01); *F23D 14/145* (2013.01); *F23D 14/18* (2013.01); *F23D 14/74* (2013.01)

(10) Patent No.:

US 9,410,699 B2

(45) **Date of Patent:**

Aug. 9, 2016

(58) Field of Classification Search

CPC F23D 14/02; F23D 14/74; F23D 14/58; F23D 14/145; F23D 14/18; F23D 14/125; F23C 3/006

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2006/0003279	A 1	1/2006	Best	431/328
2006/0292510	A1	12/2006	Krauklis et al	431/326

FOREIGN PATENT DOCUMENTS

CN 201028527 Y 2/2008 CN 201285044 Y 8/2009 (Continued)

OTHER PUBLICATIONS

Chinese Office Action, dated Nov. 11, 2015, issued in corresponding Chinese Patent Application No. 201280036562.0. Partial English translation of Search Report. Total 8 pages.

(Continued)

Primary Examiner — Alfred Basichas (74) Attorney, Agent, or Firm — Ostrolenk Faber LLP

(57) ABSTRACT

A combustion heater (110) that is provided with a heating plate (126); a placement plate (120) disposed opposite the heating plate; an outer wall (122) provided around the outer circumference of the heating plate and the placement plate; a partitioning plate (124) that is disposed opposite the heating plate and the placement plate inside a space enclosed by the heating plate, the placement plate, and the outer wall, that forms a lead-in portion (134) by a gap with the placement plate, and that forms a lead-out portion (142) by a gap with the heating plate; a linking portion (136) that links the lead-in portion and the lead-out portion; a combustion chamber (138) that combusts fuel gas at the lead-out portion near the linking portion; and a flame-stabilization portion (140) that is provided in the combustion chamber and that maintains the combustion of the fuel gas in the combustion chamber.

8 Claims, 6 Drawing Sheets

